

# Performance-PRO™ XT

## Manual Ambulance Cot



3800 E. Centre Avenue  
Portage, MI 49002 USA  
t: 269 329 2100  
toll free: 800 327 0770

[ems.stryker.com](http://ems.stryker.com)

### Standard Features

- Color-coded controls
- High visibility powder-coated frame
- Lightest-in-class, all-aluminum X-frame
- Scientifically optimized lift bar & control design
- Lower lifting bar
- Lift-capable safety bar
- Integrated bumper system
- Perforated litter surface
- One-hand release, retractable head section
- One-hand release, fold-down siderails
- One-hand release, infinite positioning, pneumatically assisted backrest
- Oversized wheels with sealed caster and wheel bearings
- G-rated bolster mattress
- Shock or flat leg positioning
- G-rated patient restraints
- Single wheel lock
- Side release handle
- Built-in pull handle
- X-frame guards
- Power washable
- Load height adjustment

### Optional Features

- Heavy duty two- or three-stage IV poles (patient right or left)
- Permanent or removable O2 bottle holders (head end, foot end or fowler)
- Defibrillator platform
- Dual wheel locks
- Pedi-Mate restraint package
- Equipment hook
- Backrest storage pouch
- Head end storage flat
- Base storage net
- Knee gatch
- Head extension
- Pillow
- Restraint extender
- Power-LOAD compatibility

### Specifications

<b>Model Number</b>	<b>6086</b>
<b>Height<sup>1</sup></b>	
Position 1	13.8 in (35.1 cm)
Position 2	22 in (55.9 cm)
Position 3	25.8 in (66.5 cm)
Position 4	28.1 in (71.4 cm)
Position 5	31.9 in (81 cm)
Position 6	34.6 in (87.9 cm)
Position 7	37.3 in (94.7 cm)
Position 8	40 in (101.6 cm)
Position 9	42.2 in (107.2 cm)
<b>Load Height Adjustment</b>	
High	Deck heights 34 in (86 cm) and above
Mid	Deck heights between 30 – 34 in (76 – 86 cm)
Low	Deck heights below 30 in (76 cm)
<b>Length</b>	
Standard	80 in (203 cm)
Minimum	64 in (163 cm)
<b>Width</b>	23 in (58 cm)
<b>Weight<sup>2</sup></b>	89 lb (40.37 kg)
<b>Wheels</b>	
Diameter	6 in (15 cm)
Width	2 in (5 cm)
<b>Articulation</b>	
Backrest	0 –73°
Shock Position	+15°
Optional Knee Gatch	30°
<b>Maximum Weight Capacity</b>	700 lb (318 kg)
<b>Minimum Operator Required</b>	
Occupied Cot	2
Unoccupied Cot	1
<b>Recommended Fastener System</b>	
Power-LOAD	Model 6390
Floor Mount	Model 6370 or 6377
Wall Mount	Model 6371
<b>Recommended Loading Height<sup>3</sup></b>	Up to 34 in (86.4 cm)

### Warranty

- One year parts and labor or two year parts only
- One-year soft goods
- Three-year X-frame components
- Lifetime on all welds\*

### Extended warranties available.

\*7-year service life.

<sup>1</sup>Height measured from bottom of mattress, at seat section, to ground level.

<sup>2</sup>Cot is weighed without mattress and restraints.

<sup>3</sup>Load height can be set between 27.25 in and 34 in.

Stryker reserves the right to change specifications without notice. In-service video included with every order.

The Performance-PRO XT is designed to conform to the Federal Specification for the Star-of-Life Ambulance KKK-A-1822.

The Performance-PRO XT is designed to be compatible with competitive cot fastener systems.

The yellow and black color scheme is a registered trademark of Stryker Corporation

Meets dynamic crash standards with Performance-LOAD cot fastening system (SAE J3027 with X-restraints).

Stryker Corporation or its divisions or other corporate affiliated entities own, use or have applied for the following trademarks or service marks: **Performance Pro, Power-LOAD, Stryker**, . All other trademarks are trademarks of their respective owners or holder.

Certifications

